



### KEY FEATURES

- Power supply on metal box of 4 output 12V /5A
- Individual fuse protection
- Overvoltage protection 5KA
- External LED indicator for each channel
- Blue case for wall installation

# CAM-622

POWER SUPPLY ON METAL BOX OF 4 OUTPUT 12V /5A

### FEATURES

- Power supply source on metal box with 4 outputs 12V /5A
- Blue case for wall installation
- Universal AC input range: 96V ~ 264V AC
- 4 channel individual fuse tube, the fuse is cut off automatically while a short circuit, a current overload or an overload occurs in a single channel and keeps the entire power system functioning correctly
- Protection against surges 5KA
- Cooling by free air convection and cooling fin
- Protection against overload, over current, overvoltage, overheating, shortcut
- External LED indicator for each channel output
- Incorporates EMI wave filter, 100% full load burn test
- Long life electrolytic capacitors 105 ° C
- High efficiency, long service life, high reliability

### SPECS

- Input voltage: 96V ~ 264V CA
- Input current: <1,5A (115V AC), <1A (230V AC)
- Input frequency range: 47 ~ 63Hz
- Input efficiency:  $\leq 85\%$
- Protection against input surges of 30A / 240V
- Output voltage of 11.5V ~ 14.5V DC
- Nominal output: 5A
- Output current range: 0 ~ 5A
- Nominal power: 60W
- 4 channels of power output
- Operating temperature: -20 ° C ~ + 70 ° C
- Operating relative humidity of 20% ~ 90%
- Storage temperature: -40 ° C ~ + 85 ° C
- Relative storage humidity of 10% ~ 95%
- Lockable box for wall mounting
- Individual protection by fuse
- Dimensions: 190 x 204 x 66 mm