

8 POE PORT 10/100M SWITCH (CCTV MODE UP TO 250M) + 1 UPLINK PORT



FEATURES

- Transmission up to 250 meters
- Compatible with IEEE 802.3af standard/at
- PoE power supply up to 15,4/25,5W per port
- Automatic connected device detection
- Plug&Play
- Great quality/price
- Use UTP CAT5 cable or superior
- Unmanageable switch (L2)

PORT DESCRIPTION	
PoE ports	8 puertos RJ45 10/100M autonegociated
Puerto Uplink	9º puerto RJ45 10/100M autonegociated
POE POWER SUPPLY	
PoE max output	30W
Total consumption	96W
PoE port priority	Supported
GENERAL	
Processing type	store and forward
Transmission model	IEEE802.3X full-duplex / Backpressure half-duplex
Backplane bandwidth	1,8Gbps
Package transference rate	1,74Mpps
MAC address	2K
Standard	IEEE802.3i 10 BASE-T, IEEE802.3u 100 BASE-TX, IEEE802.3x flux control, IEEE802.3af (PoE), IEEE802.3at (PoE+), IEEE802.3az EEE
ELECTRICAL & ENVIRONMENTAL	
Power supply	200V ~ 240V AC, 50/60Hz
Working temperature	-10°C ~ +45°C, 10% ~ 90% RH
PHYSICAL FEATURES	
Dimensions	233 x 143 x 45 mm